


SPECIFICATION:

GRATE ASSORTMENT FOR JOSAM 41500 AND 43500 TYPE 304
10" SQUARE TOP DRAINS.


SS DRAINS
10" SQUARE TOPS

SERIES 41500/43500

STANDARD PERFORATED GRATE




1 3/16
[30]



SLOT WIDTH - .31" [8]
FREE AREA - 18.0 IN²
LOAD - MEDIUM DUTY
MEETS ADA AND HEEL-PROOF REQS.

- 3Q 3/4 PERFORATED GRATE




1 3/16
[30]



SLOT WIDTH - .31" [8]
LOAD - MEDIUM DUTY

- HG PERFORATED 1/2 GRATE





1 3/16
[30]




SLOT WIDTH - .31" [8]
LOAD - MEDIUM DUTY

- MG ANTI-SLIP MESH GRATE





1 3/16
[30]




OPENINGS - .9" X .9" [23 X 23]
LOAD - MEDIUM DUTY

- LG LADDER GRATE





3/16
[4]

1 3/16
[30]



SLOT WIDTH - .8" [20]
LOAD - HEAVY DUTY

- SG PERIMETER SLOT GRATE



Ø7/8
[22]

1 3/16
[30]

3/8
[10]



SLOT WIDTH - .35" [9]
LOAD - EXTRA-HEAVY DUTY

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

DATE OF LAST CHANGE: 7/16/18

DIMENSIONS ARE SUBJECT TO MANUFACTURERS
TOLERANCES AND CHANGE WITHOUT NOTICE.
WE CAN ASSUME NO RESPONSIBILITY FOR
USE OF SUPERSEDED OR VOID DATA.

JOSAM
MICHIGAN CITY, INDIANA

NOTES